

ref. 99031784

SUBMERSIBLE PUMP K5 220V 330L/MIN

DOMPELPOMPEN MAST

Height of discharge: max. 11 m
Maximum flow rate: 330 l/min
Grit passage: 10 mm
Coupling: DSP45 with bolt
Motor: 230V - 50 Hz - 1-phase
Power P1: 810 W
Maintenance-free and dry-running protection

DESCRIPTION
Basement drainage pump
Submersible pump Mast type K5 220V with max. flow of 330 l/min, supplied with coupling DSP45 with bolt.

Applications: For demanding use with dirty water in shafts and wells. Can also be used for pumping fuel oil at room temperature (in accordance with statutory regulations).

Flow rate:
- 330 l/min - 0 m discharge height
- 300 l/min - 2 m discharge height
- 200 l/min - 6 m discharge height
- 0 l/min - 11 m discharge height

TECHNICAL SPECIFICATIONS
- Contains no silicones
- Built-in strain relief
- Motor with thermal winding protection
- Safe dry running
- Maintenance free
- Removable sieve for deeper suction (clip closure)

- Pump: Single-stage centrifugal pump
- Head: max. 11 m


Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

- Maximum flow rate: 330 l/min
- Grit passage: 10 mm
- Exhaust: diameter 1" 1/4
- Coupling: DSP45 with lock
- Temperature of pumped liquid: max 45°C (permanent), max 80°C (up to 3 min)
- Liquid density: of pumped liquid: max 1,1 kg/dm3
- Acidity of pumped liquid: pH 5-8
- Motor: 230V - 50 Hz - 1-phase
- Power P1: 810 W
- Power P2: 500 W
- Rated current: 3.7 A
- Connection cable: Length 10 m H 07 RN-F 3 G 1.0)
- Plug: Schuko IP 44
- Material carrying handle: Hard plastic (PP) (30% glass fibre reinforced), impact resistant
- Motor housing material: Stainless steel 1.4301
- Pump housing material: Hard plastic (PP) (30% glass fibre reinforced), impact resistant
- Rotor material: Stainless steel 1.4122
- Material range: polyoxymethylene (POM), high hardness, high wear resistance
- Material screws: A2 stainless steel
- Seals material: oil-resistant elastomers NBR quality
- Shaft seal material: 3-fold NBR Perbunan
- Sieve material: Hard plastic (PP) (30% glass fibre reinforced), impact resistant
- Dimensions: Dia175 x H280 mm
- Weight: 6.7 kg







Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be