

ref. 99012757

# QUADRAFOG 500 W/GRIP 1.5``BSP 100-500L/MIN 6BAR FLASHOVER

## STRAALPIJPEN TFT LAGE DRUK

Maximum working pressure: 16 bar
Possible settings flow rate: 100 / 250 / 350 / 500 (at 6bar) + flush position
Type: Selectable (not automatic)
Valve type: Ball valve
Handles available in 11 colours (standard black)

DESCRIPTION
TFT nozzle - Series Quadrafog
A compact and lightweight nozzle with high performance and robust design. Equipped with a horseshoe handle for operating the ball valve. The nozzle head has a fixed toothed ring and rubber bumper.
The nozzle is equipped with a flow control ring with tactile lock with spring ball (stand-up sensor), making it easy to set the desired flow rate. There is also a tactile marking on the head that clearly indicates the Flashover positioning.

Suitable for mounting on a low pressure reel.

TECHNICAL SPECIFICATIONS
- Range : Low pressure nozzle of the American type
- Type: Selectable (not automatic)
- Flow rate: 100 - 500 l/min (at 6 bar)
- Flow selection via flow ring
- Possible settings flow rate: 100 / 250 / 350 / 500 (at 6bar) + flush position
- Pressure Pr : 6 bar
- Pressure Pn: 16 bar
- Bursting pressure: 70 bar
- Pressure regulation: No
- Range: 40 m at 500 l/min
- Coupling: 1.5" BSP F (knurled)

**Vanassche Firefighting Engineering**
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be


**Vanassche Services**
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

- Including DSP 45 coupling
- Swivel joint (360°): Yes
- Filter (suction sieve): No
- Valve type: Ball valve
- Valve material: stainless steel
- Handle: Horseshoe handle
- Tooth wreath: Fixed - precision ground metal fog teeth
- Protective bumper: Yes
- Jet pattern: Infinitely adjustable jet pattern from full jet to water screen 130°
- Position sensor (spring loaded) on flow setting and beam pattern
- Gun grip: Yes
- Nozzle material: hard-anodised aluminium
- Standardisation: EN15182-2 Type 3
- Dimensions: 290 x 240 x 100 mm
- Weight : 1.79 kg

ACCESSORIES AND OPTIONS

- Handles available in 11 colours
- 99012806: Foam insert Heavy foam (Low expansion)
- 99012810: Foam insert Middle foam (Low and Medium expansion)









**Vanassche Firefighting Engineering**
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

**Vanassche Services**
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be