

ref. 99012759

ULTIMATIC LANCE FO7 - 7 BAR 1"1/2 F

STRAALPIJPEN TFT LAGE DRUK

Maximum working pressure 16 bar
Type: Automatic pressure / variable flow rate
Type of valve: gate valve
Handles available in 11 colours (standard black)

DESCRIPTION
TFT nozzle - Ultimatic series
Easy-to-operate nozzle with automatic pressure control at 7 bar and infinitely variable flow limitation by control of the gate valve. Suitable for indoor and outdoor fire fighting. The flow rate is easily adjusted by opening the horseshoe handle less or more.
The cylindrical stainless steel gate valve prevents pressure loss and ensures a faster response when operated, a stabilised blasting pattern and an optimum throw. The valve can be operated with a minimum of force thanks to the built-in hydraulic power.
The rotatable nozzle of the ULTIMATIC nozzles allows stepless adjustment of the spray pattern from full jet to water screen in a quarter turn. The position of the nozzle and the flow ring are clearly visible and tactile. The conical teeth of the rubber bumper create a jet cone filled with fine droplets when sprayed, with no flame suction effect.

TECHNICAL SPECIFICATIONS
- Range: Low pressure nozzle of the American type
- Type: Automatic pressure / variable flow rate
- Flow rate: 150 - 500 l/min
- Flow rate selection via Handle
- Pressure Pr: 7 bar
- Pressure Pn: 16 bar
- Pressure Pm: 7 bar
- Bursting pressure: 100 bar
- Pressure regulation: Yes
- Range: 40 m at 500 l/min
- Coupling: 1.5" BSP F (knurled)
- Including coupling: DSP 45
- Swivel joint (360°): Yes


Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

- Filter (suction strainer): Yes
- Type of valve: gate valve
- Valve material: stainless steel
- Toothed wreath: Solid - shaped rubber
- Protective bumper: Yes
- Blast pattern: Infinitely adjustable spray pattern from full spray to water screen 130° + rinsing position
- Position sensor (spring loaded) on Jet pattern
- Handle: Horseshoe handle
- Gun grip: Yes
- Nozzle material: hard-anodised aluminium
- Standardisation: EN15182-2 Type 4 / EN15182-2 Type 4
- Dimensions: 270 x 120 x 239 mm
- Weight: 1.4 kg

ACCESSORIES AND OPTIONS
- Handles available in 11 colours
- 99012801: Foam insert Heavy foam (Low expansion)
- 99012803: Foam insert Middle foam (Low and Medium expansion)







Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be