

ref. 99034272

FOAM LANCE M2/S2

SCHUIMSTRAALPIJPEN

Foam nozzle for heavy and middle foam

Flow rate: 200 l/min (at 5 bar)

Coupling: DSP45 without bolt

TECHNICAL SPECIFICATIONS:

- Type / Nominal size: S2/M2
- Purpose: Heavy and medium foam
- Choice valve heavy and middle foam
- Flow rate: 200 l/min (at 5 bar)
- Pressure Pn: 16 bar
- Input pressure: 5 bar
- Foam heavy foam: 1:10 max (*)
- Defoaming middle foam: 1:50 max (*)
- Type of valve: ball valve with pressure gauge
- Throw length heavy foam: 23 m
- Throw length middle foam: 7 m
- Coupling: DSP45 without bolt
- Dimensions: L646 x B250 x H205 mm
- Standardisation: EN 16712-3
- Weight: 5.3 kg

(*) Foaming strongly depends on the working pressure, the quality of the foaming agent and the hardness of the water.





Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be