ref. 99039693

EMULSIFIER UNISERAL FF60 - CLASS A - FUT 200L

SCHUIMPRODUCTEN KLASSE A

DESCRIPTION

Synthetic Class A foam UNISERAL FF 60 for extinguishing Class A substances (forest and roadside fires, chamber fires, tyres and vehicle fires).

Reduces the surface tension of water at a concentration of 0.05% from 70 mN/m to 28.5 mN/m. When used in concentrations of 0.5% to 3%, it is also possible to suppress flammable vapours.

It is a low and medium expansion foam concentrate.

Recommended dosage:

- for wetting application: 0.3 to 3%
- for foam application: 0.6 to 1%
- Extinguishing hydrocarbons: 1%

TECHNICAL SPECIFICATIONS

Typical physiochemical properties at 20°C

- Type: synthetic concentrate
- Can be rinsed with: clean water, brackish water or salt water
- Ratio: from 0.05%
- Density: 1,016 g/ml ± 0,01
- Acidity: pH 8.0 ± 1
- Surface tension (0.05% solution):: 28.5 mN/m
- Freezing point: < -15°C
- Biodegradability: 100% in 28 days
- Standardisation: EN 1568:2008
- Packaging: 200 litre drums

(price per litre)

Vanassche Firefighting Engineering
Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services
Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be